



Cargo On The Go



Wooden Cargo

Business On Wheels



High-Roof Retail Van



Mobile Café



Mobile Stage

Freshness On The Move



Box Van



Refrigerated Van



Chiller Van



Frozen Food Van

Feast For Foodies



Luton Van



Hawker Van



Aluminium Hawker Van



Pasar Tani Mobile

On-the-road Versatility



Steel Cargo



Utility Van



Utility Pick-up



Flatbed Top Pick-up

Special Purpose Mobiles



Fiberglass Canopy Pick-up



Pest Control Van



Security Van

Designed for your business

The new Daihatsu Gran Max is the ideal combination of performance, comfort and safety for wherever your business takes you.

Available in different body types to cater to various business needs.

DAIHATSU GRAN MAX	VAN	PICK-UP
Rear Wheel Drive	✓	✓
Panel Shift Lever	✓	✓
1.5 litre DWT engine	✓	✓
Power steering	✓	✓
Denso Air Conditioner	✓	✓
Anti-Lock Braking System	✓	✓
Dual-sided access to cargo area	✓	

- REAR WHEEL DRIVE
- POWER STEERING
- PANEL SHIFT LEVER
- DENSO AIR CONDITIONER
- SMALL TURNING RADIUS
- ANTILOCK BRAKING SYSTEM


BRANCH / DEALER'S STAMP



GRAN MAX

5-seater
SEMI-PANEL VAN
5座位
客货车

MORE PASSENGER, LESS CARGO.
乘客多，货物少。



TECHNICAL SPECIFICATIONS 技术规格

ENGINE 引擎

Engine	引擎	3SZ-VE
Engine Type	引擎型式	Petrol, Inline 4-Cylinder, 16-Valve, DOHC, DVVT, EFI 汽油, 同轴4汽缸, 16气门, DOHC, DVVT, EFI
Bore x Stroke	口径 x 冲程	72.0 mm x 91.8 mm
Total Displacement	排气量	1,495 cc
Compression Ratio	压缩比率	10.0
Max. Output	最高输出	71 kw / 6000 rpm
Max. Torque	最高扭力	134 Nm / 4400 rpm

TRANSMISSION 变速器

Clutch Type	离合器型式	Dry Single Plate Diaphragm Spring 干式单片隔膜弹簧
Gear Box	牙箱	Forward 5-Speed Manual, All Synchronesh 5前速手排全同步器式变速
Gear Ratio	牙档比例	1st 1档 : 3.769 2nd 2档 : 2.045 3rd 3档 : 1.376 4th 4档 : 1.000 5th 5档 : 0.838 Reverse 后退 : 4.128 Final 最终齿轮比 : 4.875

DIMENSIONS DIMENSI

Overall Length	全长	4045 mm
Overall Width	全宽	1665 mm
Overall Height	全高	1900 mm
Wheelbase	轮距	2650 mm
Track - Front	前轮辙	1460 mm
Track - Rear	后轮辙	1440 mm
Min. Road Clearance	最低离地距	165 mm
Kerb Weight	车低盘重量	1130 kg
Gross Vehicle Weight	车身连载荷重量	2000 kg
Min. Turning Radius	最低回转半径	9.4 mm

OTHERS LAIN-LAIN

Steering Type	驾驶盘	Power Assisted, Rack and Pinion 动力驾驶盘, 齿条齿轮式
Brake System	煞车系统	Hydraulic, Front-rear Split Circuit with ABS 水压式, 前后独立运动的ABS煞车系统
Brake - Front	前制动器	13-inch Ventilated Discs Brakes 13寸通风碟式煞车
Brake - Rear	后制动器	Drum Brakes, Leading and Trailing 领从蹄式鼓碟
Suspension - Front	前轮悬置	McPherson Strut with Coil Spring 配置圆柱螺旋弹簧的McPherson摆臂悬挂系统
Suspension - Rear	后轮悬置	5-link Coil Spring 五连杆螺旋弹簧悬挂系统
Fuel Tank Capacity	油轮容量	43 Litre 公升
Tyre Size	轮胎	165R13C

BRANCH / DEALER'S STAMP
分行 / 销售商盖章



DAIHATSU (MALAYSIA) SDN. BHD. (55324-H)
(A subsidiary of MBM Resources Berhad - 284496-V)
HEAD OFFICE (Spare Parts/Service Centre): Lot 1, Jalan Keluli, Section 15, 40200
Shah Alam, Selangor. Tel: 03-5510 9988 / 7969 Fax: 03-5510 8872 Hotline: 03-5510 1399

DAIHATSU
THE POWER TO MOVE